

# 1<sup>ST</sup> COOLING INC

When your air goes out...Give us a shout!

## 1SK-1411

### 14,000 BTU/hr (1.2 Ton)

## Specifications

### Electrical Data:

Voltage/Phase/Hertz	115/1/60
Amperage	13.8
Fuse Size (Amps)	20
Watts	1563
NEMA plug	5-20

**Refrigerant / Ounces** R-22 / 33

**Evaporator (CFM)** Hi – 400 Lo – 265

**Condenser (CFM)** Hi – 610 Lo – 450

**Dimensions - L x W x H (in)** 25 x 24 x 34.25

**Weight (net/ship in lbs)** 185 / 210

**Condensate Tank (US Gal)** 5

**Operating Temperature (°F)** 65 – 105



\* Optional 4 inch nozzle kit shown.

Perfect for:

Computer rooms and telephone rooms, restaurants, laboratories, factories, and retail shops. Removing moisture to bring construction sites to a work-ready state. It can also be used for back-up cooling or as an emergency stand-by unit.

## Features and Benefits

- **Heavy-duty caster wheels makes unit easy to move**
- **High-pressure reset**
- **Adjustable Thermostat to set temp to desired setting**
- **4-way Adjustable Grills to direct cold airflow**
- **Easy access to condensate tank allows quick dumping of condensate**
- **Condensate level-detection system**

## Optional Accessories

- **Condenser (hot) air exhaust ceiling kit**
- **Condensate pump**
- **4" nozzle kit**
- **Condenser air return plenum**

1ST COOLING, INC.

3201 Skylane Dr, Suite 116

Carrollton, TX 75006

972-447-0555 Direct

888-604-COOL (2665) Toll Free

972-692-6693 Fax

[www.1stcooling.com](http://www.1stcooling.com)