

1ST COOLING INC

When your air goes out.....Give us a shout!

1SSC-14423

144,000 BTU/hr (12 Ton)

Specifications

Electrical Data:

Voltage/Phase/Hertz	230 / 60 / 3
Amperage	74
Fuse Size (Amps)	91.2
Watts	20,000
NEMA plug	Camlock
Min-max voltage	200-240
Power cord gauge	4
Power cord length	110

Refrigerant (Type / Pounds) R-22 / 32.5

Evaporator (CFM) 4800

Condenser (CFM) 3900

Dimensions - L x W x H (in) 68 x 46 x 59

Weight (net in lbs) 1200

Operating Temperature (°F) -30 to 105



Perfect for:

Aircraft, factories, and numerous areas can be cooled by its indicated cooling capacity. Supporting permanent HVAC systems during rehab and retrofit operations. It can also be used for back-up cooling or as an emergency stand-by unit.

Features and Benefits

- **Performs at a wide range of temperatures and altitudes**
- **Programmable Thermostat to set temp to desired setting**
- **14" cold air flange**
- **Compressor overload relay**
- **High-pressure switch**

Optional Accessories

- **Heat strip**
- **Remote Electronic / Programmable Thermostat**
- **Condensate pump**

1ST COOLING, INC.
3201 Skylane Dr, Suite 116
Carrollton, TX 75006

972-447-0555 Direct 888-604-COOL (2665) Toll Free 972-692-6693 Fax
www.1stcooling.com