

# 1<sup>ST</sup> COOLING INC

When your air goes out.....Give us a shout!

## 1ST-1211

### 14,000 BTU/hr (1.2 Ton)

## Specifications

### Electrical Data:

Voltage/Phase/Hertz	115/1/60
Amperage	11.7
Fuse Size (Amps)	15
Watts	1300
NEMA plug	5-15

**Refrigerant (Type / Ounces)** R-22 / 32

**Evaporator (CFM)** 350

**Condenser (CFM)** 500

**Dimensions - L x W x H (in)** 26 x 20 x 34

**Weight (net/ship in lbs)** 163/205

**Condensate Tank (US Gal)** 5

**Operating Temperature (°F)** 65 – 105



Perfect for:

Computer rooms and telephone rooms, restaurants, laboratories, factories, and retail shops. Removing moisture to bring construction sites to a work-ready state. It can also be used for back-up cooling or as an emergency stand-by unit.

## Features and Benefits

- **Heavy-duty caster wheels makes unit easy to move**
- **High-pressure safety switch to protect the compressor**
- **Adjustable Thermostat to set temp to desired setting**
- **Easy access to condensate tank allows quick dumping of condensate**
- **Condensate level-detection system**

## Optional Accessories

- **Ceiling (hot) air exhaust ceiling kit**
- **Condenser air return plenum**
- **4" nozzle kit**
- **Condensate pump**

1ST COOLING, INC.

3201 Skylane Dr, Suite 116

Carrollton, TX 75006

972-447-0555 Direct

877-604-COOL (2665) Toll Free

972-692-6693 Fax

[www.1stcooling.com](http://www.1stcooling.com)