

# 1<sup>ST</sup> COOLING INC

When your air goes out.....Give us a shout!

## 1ST-2421

**29,600 BTU/hr (2.5 Ton)**

### Specifications

#### **Electrical Data:**

Voltage/Phase/Hertz	230 / 60 / 1
Amperage	12.5
Fuse Size (Amps)	20
Watts	2900
NEMA plug	6-20

**Refrigerant (Type / Ounces)** R-22 / 54

**Evaporator (CFM)** 750

**Condenser (CFM)** 1000

**Dimensions - L x W x H (in)** 25 x 24 x 34.25

**Weight (net/ship in lbs)** 251 / 305

**Condensate Tank (US Gal)** 5

**Operating Temperature (°F)** 65 – 105



Perfect for:

Large computer rooms and telephone rooms, laboratories, factories, and numerous areas can be cooled by its indicated cooling capacity. Supporting permanent HVAC systems during rehab and retrofit operations, cooling plant turnarounds, production processing and retooling. It can also be used for back-up cooling or as an emergency stand-by unit.

### Features and Benefits

- ***Fits through standard doorway 32" wide***
- ***Performs at a wide range of temperatures and altitudes***
- ***Adjustable Thermostat to set temp to desired setting***
- ***Easy access to condensate tank allows quick dumping of condensate***
- ***Condensate level-detection system***

### Optional Accessories

- ***Condenser (hot) air exhaust ceiling kit***
- ***Condenser air return plenum***
- ***Evaporator air return plenum***
- ***6" nozzle kit***
- ***Condensate pump***
- ***Electronic/Programmable Thermostat***

1ST COOLING, INC.

3201 Skylane Dr, Suite 116

Carrollton, TX 75006

972-447-0555 Direct

888-604-COOL (2665) Toll Free

972-692-6693 Fax

[www.1stcooling.com](http://www.1stcooling.com)